

5TH CATEGORY - HISTORIC RACING GROUP N APPROVED VEHICLE SPECIFICATION

This form details the approved specifications of individual vehicle models in the 5th Category Historic car group. To be issued with an Historic Log Book, cars need to comply with these specifications, the physical appearance shown in the illustrations and the general historic rules as detailed in the current Motorsport Australia Manual.

Make of Car:	Triumph	Model:	Mark 1 2000
Period of Original Manufacture:	1964 - 1969		
Motorsport Australia Historic Group:	Nc		
Date of Issue of this Document:	1 January 2024		



Refer to The Manual, Historic Appendix, Vehicle Eligibility, General Requirements & Historic Touring Cars Group N Regulations for permitted modifications.

Update Log				
1/1/2024	Inclusion of kerb and minimum racing weights			

undata loa

1.1. CHASSIS

Description:	Unitary construction
Period of Manufacture:	1964 – 1969
Manufacturer:	Triumph/AMI
Chassis Number From:	N/A
Chassis Number location:	Engine bay
Material:	Steel
Comments	None

1.2. FRONT SUSPENSION

Description:	Independent - by N	Independent - by McPherson strut				
Spring Medium:	Coil	Coil				
Damper Type:	Telescopic - Intern	Telescopic - Internal		No		
Anti-sway bar:	Fitted	Fitted		No		
Suspension adjustable:	Yes	Yes Method:		per and toe		
Comments:	Refer Appendix A					

1.3. REAR SUSPENSION

Description:	Independent	Independent - Trailing Arms				
Spring Medium:	Coil	Coil				
Damper Type:	Telescopic	Telescopic Adjustable: No				
Anti-sway bar:	Not Fitted	Not Fitted		N/A		
Suspension adjustable:	Yes	Yes Method:		t		
Comments:	Refer Appen	dix A				

1.4. STEERING

Туре:	Rack and pinion	Make:	Triumph
Comments	None		

1.5. BRAKES

	Front	Rear			
Туре:	Disc, solid	Drum			
Dimensions:	248 mm x 12.6 mm	228 mm x 44 mm			
Material of drum/disc:	Cast iron	Cast iron			
No. cylinders/pots per wheel:	Тwo	One			
Actuation:	Hydraulic	Hydraulic			
Caliper make:	Girlock				
Caliper type:	Sliding	Sliding			
Material:	Cast iron	Cast iron			
Master cylinder make:	Girlock				
Туре:	Tandem				
Adjustable bias:	No				
Servo Fitted:	Yes	Yes			
Comments:	None				

2.1. ENGINE

Make:	Triumph	Triumph			
Model:	2000				
No. cylinders:	6	Configuration:	In-line		
Cylinder Block-material:	Cast Iron	Two/Four Stroke:	Four		
Bore - Original:	74.7mm	Max allowed:	76.2 mm		
Stroke - original:	76mm	Max allowed:	76 mm		
Capacity - original:	1998 cc	Max allowed:	2080 cc		
Identifying marks:	First two letters are	MB			
Cooling method:	Liquid				
Comments:	None				

2.2. CYLINDER HEAD

Make:	Triumph					
No. of valves/cylinder:	Two	Inlet:	One	Exhaust:	One	
No. of ports total:	Twelve	Inlet:	Six	Exhaust:	Six	
No. of camshafts:	One	Location:	Block	Drive:	Chain	
Valve actuation:	Pushrod	Pushrod and rockers				
Spark plugs/cylinder:	One					
Identifying marks:	N/A					
Comments:	None					

2.3. LUBRICATION

Method:	Wet sump	Oil tank location:	N/A
Dry sump pump type:	N/A	Location:	N/A
Oil cooler standard:	No	Location:	N/A
Comments:	None		

2.4. IGNITION SYSTEM

Туре:	Points, coil and distributor
Make:	Lucas
Comments	Breakerless electronic ignition permitted

2.5. FUEL SYSTEM

Carburettor Make:	SU	Model:	HS4	
Carburettor Number:	Two			
Size:	1.5″			
Fuel injection Make:	N/A	Туре:	N/A	
Supercharged:	No	Туре:	N/A	
Comments:	None	· · ·	· · ·	

SECTION 3 - TRANSMISSION

3.1. CLUTCH

Make:	Various
Туре:	Diaphragm
Diameter:	216 mm
No. of Plates:	One
Actuation:	Hydraulic
Comments:	None

3.2. TRANSMISSION

Туре:	Synchromesh			
Make:	Triumph			
Gearbox location:	Behind engine			
No. forward speeds:	Four (overdrive optional)			
Gearchange type and location:	H pattern floor mounted			
Case material:	Cast iron			
Identifying marks:	N/A			
Comments:	None			

3.3. FINAL DRIVE

Make:	Triumph	Model:	N/A
Туре:	Live axle		
Ratios:	Various		
Differential type:	Hypoid bevel		
Comments:	None		

3.4. TRANSMISSION SHAFTS (EXPOSED)

Number:	Three		
Location:	Gearbox to final drive		
Description:	One open tail shaft, two halfshafts with slip joints		
Comments:	Component substitution for rear hubs and half shafts allowed.		
	Refer Appendix B		

3.5. WHEELS & TYRES

-

Wheel type - Original:	Pressed disc	Material - Original:	Steel	
Wheel type - Allowed:	Steel	Material - Allowed:	Steel	
	Alloy (period style)		Alloy	
Fixture method:	Stud and nut	No. studs:	Four	
Wheel dia. & rim width	FRONT		REAR	
Original:	5″ x 13″		5" x 13"	
Allowed	6" x 13"		6" x 13"	
Tyre Section:				
Allowed:	Refer approved tyre list.			
Aspect ratio - minimum:	60% minimum aspect ratio.			
Comments:	None			

SECTION 4 GENERAL

4.1. FUEL SYSTEM

Tank Location:	Under boot floor	Capacity:	64 Litres
Fuel pump, type:	Electric	Make:	Lucas
Comments:	None		

4.2. ELECTRICAL SYSTEM

Voltage:	12	Alternator fitted:	Alternator
Battery Location:	Engine bay		
Comments:	None		

4.3. BODYWORK

Туре:	Sedan	Material:	Steel
No. of seats:	Five	No. doors:	Four
Comments:	None		

4.4. DIMENSIONS

Track - Front:	1330 mm	Rear:	1340 mm
Wheelbase:	2690 mm	Overall length:	4419 mm
Approved Manufacturer's	1170 kgs		
kerb weight:			
Approved minimum racing	1147 kgs		
weight:			
Comments:	None		

4.5. SAFETY EQUIPMENT

Refer applicable Group Regulations

Appendix A

Suspension

Front

Spring height adjustment permitted.

Rear

Spring height adjustment permitted.

Appendix B

Rear hub and half shafts

Rear hub and half shaft component substitution allowed due to safety (rear hubs), and half shafts due to availability.

Modified Datsun 1600 type with Heavy-duty hub.



Or

Twin CV with heavy-duty hub.

