

5TH CATEGORY - HISTORIC RACING

GROUP N

APPROVED VEHICLE SPECIFICATION

This form details the approved specifications of individual vehicle models in the 5th Category Historic car group. To be issued with an Historic Log Book, cars need to comply with these specifications, the physical appearance shown in the illustrations and the general historic rules as detailed in the current Motorsport Australia Manual.

Make of Car:	Volvo	Model:	122
			Amazon
Period of Original Manufacture:	1956 – 1970		
Motorsport Australia Historic Group:	: Nb		
Date of Issue of this Document:	30 September 2021		
Comments	s 1956 – B16 engine		
	1961 – B18 engine and front disc brakes		
	1969 – B20 engine		



Refer to Motorsport Australia Manual of Motor Sport, Vehicle Eligibility, Historic Touring Cars, General Requirements & Nc Regulations for permitted modifications.

Update Log			

SECTION 1 - CHASSIS

1.1. CHASSIS

Description:	Unitary construction	
Period of Manufacture:	1956 – 1970	
Manufacturer:	Volvo	
Chassis Number From:	***** _ *****	
Chassis Number location:	Bulkhead – engine bay	
Material:	Steel	
Comments	None	

1.2. FRONT SUSPENSION

Description:	Independen	Independent – upper and lower wishbones			
Spring Medium:	Coil	Coil			
Damper Type:	Telescopic	Telescopic Adjustable: No			
Anti-sway bar:	Yes		Adjustable:	No	
Suspension adjustable:	Yes	Yes Method: Caster, camber and toe			
Comments:	Refer to App	Refer to Appendix A			

1.3. REAR SUSPENSION

Description:	Live rear axle	Live rear axle			
Spring Medium:	Coil				
Damper Type:	Telescopic		Adjustable:	No	
Anti-sway bar:	No	No		No	
Suspension adjustable:	No	Method:	N/A		
Comments:	Refer to Appe	ndix A			

1.4. STEERING

Type:	Cam and roller	Make:	Volvo
Comments	None		

1.5. BRAKES

	Front	Rear		
Type:	Disc, solid	Drum		
Dimensions:	276 mm x 25 mm	294 mm x 51 mm		
Material of drum/disc:	Cast iron	Cast iron		
No. cylinders/pots per wheel:	Two	Two		
Actuation:	Hydraulic	Hydraulic		
Caliper make:	Volvo			
Caliper type:	N/A			
Material:	N/A			
Master cylinder make:	Volvo			
Туре:	Tandem			
Adjustable bias:	No			
Servo Fitted:	Yes			
Comments:	None			

SECTION 2 - ENGINE

2.1. ENGINE

Make:	Volvo	Volvo				
Model:	B16, B18	B16, B18				
No. cylinders:	Four	Configuration:	In line			
Cylinder Block-material:	Cast iron	Two/Four Stroke:	Four			
Bore - Original:	84.14 mm	84.14 mm Max allowed: 85.6 mm				
Stroke - original:	80 mm	Max allowed:	80 mm			
Capacity - original:	1780 cc	Max allowed:	1843 cc			
Identifying marks:	Left side of the engine bloc	k				
Cooling method:	Liquid					
Comments:	None					

2.2. CYLINDER HEAD

Make:	Volvo					
No. of valves/cylinder:	Two	Inlet:	One	Exhaust:	One	
No. of ports total:	Eight	Inlet:	Four	Exhaust:	Four	
No. of camshafts:	One	Location:	Block	Drive:	Gear	
Valve actuation:	Pushrod	Pushrod and rocker				
Spark plugs/cylinder:	One					
Identifying marks:	N/A					
Comments:	None					

2.3. LUBRICATION

Method:	Wet sump	Oil tank location:	N/A
Dry sump pump type:	N/A	Location:	N/A
Oil cooler standard:	No	Location:	N/A
Comments:	None		

2.4. IGNITION SYSTEM

Type:	Points, distributor & coil	
Make:	Bosch	
Comments	Breakerless electronic ignition permitted	

2.5. FUEL SYSTEM

Carburettor Make:	SU	Model:	Н	
			HS	
Carburettor Number:	Two			
Size:	Various			
Fuel injection Make:	N/A	Type:	N/A	
Supercharged:	No	Type:	N/A	
Comments:	None		·	

SECTION 3 - TRANSMISSION

3.1. CLUTCH

Make:	Volvo
Type:	Diaphragm
Diameter:	216 mm
No. of Plates:	One
Actuation:	Hydraulic
Comments:	None

3.2. TRANSMISSION

Type:	Synchromesh
Make:	Volvo
Gearbox location:	Behind engine
No. forward speeds:	Four
Gearchange type and location:	Floor - direct
Case material:	Cast iron
Identifying marks:	N/A
Comments:	None

3.3. FINAL DRIVE

Make:	Vovlo	Model:	Amazon
Type:	Live rear axle		
Ratios:	Various		
Differential type:	Hypoid bevel		
Comments:	None		

3.4. TRANSMISSION SHAFTS (EXPOSED)

Number:	One
Location:	Gearbox to final drive
Description:	Open tail shaft with twin uni joints
Comments:	None

3.5. WHEELS & TYRES

Wheel type - Original:	Pressed disc	Materia	l - Original:	Steel
Wheel type - Allowed:	Steel	Materia	l - Allowed:	Steel
	Alloy (period style)			Alloy
Fixture method:	Stud and nut	No. stud	s:	Five
Wheel dia. & rim width	FRONT		REAR	
Original:	4" x 15" 4" x 15			4" x 15"
Allowed	6" x 15" 6" x 15"			6" x 15"
Tyre Section:				
Allowed:	Refer approved tyre list.			
Aspect ratio - minimum:	60% minimum aspect ratio.			
Comments:	None			

SECTION 4 GENERAL

4.1. FUEL SYSTEM

Tank Location:	Rear	Capacity:	45 litres
Fuel pump, type:	Mechanical on block	Make:	Volvo
Comments:	None		

4.2. ELECTRICAL SYSTEM

Voltage:	12	Alternator fitted:	Generator
Battery Location:	Engine bay		
Comments:	None		

4.3. BODYWORK

Туре:	Sedan	Material:	Steel
No. of seats:	Four	No. doors:	2 or 4 door
Comments:	None		

4.4. DIMENSIONS

Track - Front:	1315 mm	Rear:	1315 mm
Wheelbase:	2600 mm	Overall length:	4450 mm
Dry weight:	1013 Kg		
Comments:	None		

4.5. SAFETY EQUIPMENT

Refer applicable Group Regulations

Appendix A

Group Nb must use early rear trailing arms with axle tube surround bush.

Suspension

Front

Spring height adjustment permitted.

Rear

Spring height adjustment permitted.