

5TH CATEGORY - HISTORIC RACING

GROUP S

APPROVED VEHICLE SPECIFICATION

This form details the approved specifications of individual vehicle models in the 5th Category Historic car group. To be issued with an Historic Logbook, cars need to comply with these specifications, the physical appearance shown in the illustrations and the general historic rules as detailed in the current Motorsport Australia Manual.

Make of Car:	Alfa Romeo	Model:	Montreal
Period of Original Manufacture:	1970 – 1977		
Motorsport Australia Historic Group:	Sc		
Date of Issue of this Document:	30/6/2022		



Update Log

30/6/2022	Document layout

SECTION 1 - CHASSIS

1.1. CHASSIS

Description:	Unitary construction
Period of Manufacture:	1970 – 1977
Manufacturer:	Alfa Romeo
Chassis Number From:	AR1425101X
Chassis Number location:	Firewall
Material:	Steel
Comments	None

1.2. FRONT SUSPENSION

Description:	Independer	Independent by upper and lower wishbone			
Spring Medium:	Coil	Coil			
Damper Type:	Telescopic	Telescopic Adjustable: Optional			
Anti-sway bar:	Yes	Yes		Optional	
Suspension adjustable:	Yes	Yes Method: Adjustable upper control arm			
Comments:	Spring rates	Spring rates and ride heights may be adjusted			

1.3. REAR SUSPENSION

Description:	Live axle with	Live axle with upper and lower trailing arms				
Spring Medium:	Coil	Coil				
Damper Type:	Telescopic	Telescopic		Optional		
Anti-sway bar:	Fitted	Fitted		Optional		
Suspension adjustable:	Yes	Yes Method:				
Comments:	None					

1.4. STEERING

Type:	Recirculating ball	Make:	Alfa Romeo
Comments	None		

1.5. BRAKES

	Front	Rear		
Туре:	Disc	Disc		
Dimensions:	272 mm x 22 mm	267 mm x 20 mm		
Material of drum/disc:	Cast iron	Cast iron		
No. cylinders/pots per wheel:	Two	Two		
Actuation:	Hydraulic	Hydraulic		
Caliper make:	ATE			
Caliper type:	Tandem			
Material:	Cast iron			
Master cylinder make:	ATE			
Type:	Single			
Adjustable bias:	No			
Servo Fitted:	Yes			
Comments:	Dual or tandem master cylinders permitted			

SECTION 2 - ENGINE

2.1. ENGINE

Make:	Alfa Romeo		
Model:	105.65		
No. cylinders:	Eight	Configuration:	Vee
Cylinder Block-material:	Aluminium	Two/Four Stroke:	Four
Bore - Original:	80 mm	Max allowed:	81.5 mm
Stroke - original:	64.5 mm	Max allowed:	64.5 mm
Capacity - original:	2593 cc	Max allowed:	2690 cc
Identifying marks:	105.65		
Cooling method:	Liquid		
Comments:	None		

2.2. CYLINDER HEAD

Make:	Alfa Romeo				
No. of valves/cylinder:	Two	Inlet:	One	Exhaust:	One
No. of ports total:	Sixteen	Inlet:	Eight	Exhaust:	Eight
No. of camshafts:	Four	Location:	Heads	Drive:	Chain
Valve actuation:	Buckets				
Spark plugs/cylinder:	One				
Identifying marks:					
Comments:	None				

2.3. LUBRICATION

Method:	Dry sump	Oil tank location:	Engine bay
Dry sump pump type:		Location:	Engine bay
Oil cooler standard:	Yes	Location:	Front
Comments:	None		

2.4. IGNITION SYSTEM

Туре:	Electronic
Make:	Capacitor discharge
Comments	None

2.5. FUEL SYSTEM

Carburettor Make:		Model:		
Carburettor Number:				
Size:				
Fuel injection Make:	Spica	Туре:	Mechanical	
Supercharged:	No	Туре:	N/A	
Comments:	None			

SECTION 3 - TRANSMISSION

3.1. CLUTCH

Make:	Various
Type:	Dry plate
Diameter:	228 mm
No. of Plates:	One
Actuation:	Hydraulic
Comments:	Clutch and method of acutation are free

3.2. TRANSMISSION

Type:	5 speed synchromesh
Make:	ZF
Gearbox location:	Behind engine
No. forward speeds:	Five
Gearchange type and location:	Floor romte
Case material:	Aluminium
Identifying marks:	
Comments:	Gear rtios are free

3.3. FINAL DRIVE

Make:	Alfa Romeo	Model:	105
Wheel drive method	Rear		
Ratios:	Various		
Differential type:	Spin resistant, hypoid		
Comments:	None		

3.4. TRANSMISSION SHAFTS (EXPOSED)

Number:	One
Location:	Gearbox to final drive
Description:	Tubular shaft with Hardie Spicer type universal joints
Comments:	None

3.5. WHEELS & TYRES

Wheel type - Original:	Campagnolo	Material - Original:		Magnesium alloy	
	Alfa Romeo				
Wheel type - Allowed:	Period alloy	Material	- Allowed:	Period alloy	
Fixture method:	Suds and nuts	No. stud	s:	Four	
Wheel dia. & rim width	FRONT			REAR	
Original:	6.5" x 14"		(6.5" x 14"	
Allowed	7" x 15"		7" x 15"		
Tyre Section:					
Original:	195/70 x 14"	95/70 x 14" 195/70 x 14"		95/70 x 14"	
Allowed:	215/60 x 14"		21	L5/60 x 14"	
	225/60 x 14"		225/60 x 14"		
Aspect ratio - minimum:	60% minimum aspect ratio.				
Comments:	Refer approved tyre list.				

SECTION 4 GENERAL

4.1. FUEL SYSTEM

Tank Location:	Rear	Capacity:	63 litres
Fuel pump, type:	Electric x 2	Make:	Bosch
Comments:	Fuel pumps are free		

4.2. ELECTRICAL SYSTEM

Voltage:	Twelve	Alternator fitted:	Alternator
Battery Location:	Boot		
Comments:	None		

4.3. BODYWORK

Type:	Fixed head Coupe	Material:	Steel
No. of seats:	Two x two	No. doors:	Two
Comments:	None		

4.4. DIMENSIONS

Track - Front:	1372 mm	Rear:	1340 mm
Wheelbase:	2350 mm	Overall length:	4220 mm
Dry weight:	1220 kg		
Comments:	None		

4.5. SAFETY EQUIPMENT

Refer applicable Group Regulations

Appendix